




Dispense Valve Selection Guide

Nordson
EFD



Choosing the right dispense valve for an application starts with the fluid.

Use this guide to:

- See which Nordson EFD valves work with specific fluids and applications
- Compare the features of EFD valves and controllers
- Select a type of fluid for an application

For example, if you know you want to use a jet dispensing valve because of its significant precision and fast cycle rate, you could use this guide to identify the types of fluids most suitable for jetting.

Benefits

- Performance that's proven for millions of dispense cycles
- Long service life with minimal maintenance
- Worldwide technical assistance
- Global application testing labs

Please note this guide does not include every EFD dispensing solution available. It's important to speak with an experienced EFD application specialist when choosing the right solution for your application.

APPLICATION DEFINITIONS



Microdots

Any deposit having a volume less than 5 μ l.
(5 μ l = 5 microliters = 5/1000 cc)



Dots

Any deposit having a volume larger than 5 μ l.



Jetting

Applying microdots, dots, lines, stripes, and encapsulates without making contact with a surface—also called non-contact dispensing.



Potting

Filling a cavity usually containing an electronic device, electronic circuit or wires.



Encapsulating

Applying a coating to an electronic component for protection from mechanical or environmental damage.



Lines / Stripes

A line, bead or stripe of material.



Filling / Packaging

Filling containers such as small bottles, cartridges and tubes.



Microspray

Narrow spray pattern capability as small as 1 mm (0.04") wide.



Spray

Applying fluids using low pressure air to break the fluid into fine droplets for coating or marking.




Internal Spray


Spraying the inside diameter of holes and cylinders.


FLUIDS	VALVE APPLICATIONS										
	Microdots*	Dots	Jetting	Potting	Encapsulating	Lines/Stripes	Filling / Packaging	Microspray	Spray	Internal Spray	Internal Band
Accelerators	xQR41	752V-UHSS	PICO Ppulse / XP P-Jet, P-Dot	—	—	xQR41V	752V-UHSS	781Mini	781S-SS	782RA	7860C-RS
Activators	xQR41	752V-UHSS	PICO Ppulse / XP P-Jet, P-Dot	—	—	xQR41V	752V-UHSS	781Mini	781S-SS	782RA	7860C-RS
Alcohol	xQR41	752V-UHSS	PICO Ppulse / XP P-Jet	—	—	xQR41V	752V-UHSS	781Mini	781S-SS	782RA	7860C-RS
Anaerobics	xQR41 PEEK** 752V-UHSS	xQR41 PEEK** 752V-UHSS	PICO Ppulse / XP P-Jet	—	—	752V-UHSS	725HF-A	—	—	—	7860C-RS
Conformal Coatings	xQR41	752V-UHSS	PICO Ppulse / XP P-Jet	—	752V-UHSS	752V-UHSS	725HF-SS	781Mini	781S-SS	—	—
Copper Braze Paste	—	725DA-SS	—	—	—	725DA-SS	725HF-SS	—	—	—	—
Cyanoacrylates	xQR41 PEEK** 752V-UHSS	xQR41 PEEK** 752V-UHSS	PICO Ppulse / XP P-Jet, P-Dot	—	—	752V-UHSS	—	—	—	—	7860C-RS
Electrolytes	xQR41	752V-UHSS	PICO Ppulse / XP P-Jet	—	—	—	752V-UHSS	781Mini	781S-SS	—	—
Epoxies	xQR41	752V-UHSS	PICO Ppulse / XP P-Dot	725DA-SS	725DA-SS	725DA-SS	725HF-SS	—	—	—	—
Fluxes, Liquid	xQR41	752V-UHSS	PICO Ppulse / XP P-Jet	—	—	752V-UHSS	725HF-SS	781Mini	781S-SS	—	—
Fluxes, Paste	xQR41	725DA-SS	PICO Ppulse / XP P-Jet, P-Dot	—	—	725DA-SS	725HF-SS	—	—	—	—
Grease: low pressure <i>(to 7.0 bar, 100 psi)</i>	xQR41	725DA-SS	PICO Ppulse / XP P-Jet, P-Dot	—	—	725DA-SS	725HF-SS	—	781S-SS	—	—
Grease: med. pressure <i>(to 20.7 bar, 300 psi)</i>	xQR41	736HPA-NV	PICO Ppulse / XP P-Jet, P-Dot	—	—	736HPA-NV	736HPA-NV	—	781S-SS	—	—
Grease: high pressure <i>(to 172 bar, 2500 psi)</i>	—	736HPA-NV	PICO Ppulse / XP P-Jet, P-Dot	—	—	736HPA-NV	736HPA-NV	—	—	—	—
Inks / Paints	xQR41	752V-UHSS	PICO Ppulse / XP P-Jet	—	—	xQR41V	725HF-SS	781Mini	781S-SS	782RA	7860C-RS
Oils	xQR41	752V-UHSS	PICO Ppulse / XP P-Jet, P-Dot	—	—	xQR41V	725HF-SS	781Mini	781S-SS	782RA	7860C-RS


*Note: For microdot applications requiring general purpose tip sizes between 27 and 33 gauge, specify valve model xQR41 in place of 741V-SS. **Conditional use with cyanoacrylates.


Application Definitions

 **Microdots:** Any deposit having a volume less than 5 µl (5 µl = 5 microliters = 5/1000 cc).

 **Dots:** Any deposit having a volume larger than 5 µl.


 **Jetting:** Applying microdots, dots, lines, stripes, and encapsulates without making contact with a surface – also called non-contact dispensing.

 **Potting:** Filling a cavity usually containing an electronic device, electronic circuit, or wires.

 **Encapsulating:** Applying a coating to an electronic component for protection from mechanical or environmental damage.

 **Lines/Stripes:** A line, bead or stripe of material.

 **Filling/Packaging:** Filling containers such as small bottles, cartridges, and tubes.

 **Microspray:** Narrow spray pattern capability as small as 1 mm (0.04") wide.

















 **Spray:** Applying fluids by using low pressure air to break the fluid into fine droplets for coating or marking.

 **Internal Spray:** Spraying the inside diameter of holes and cylinders.

FLUIDS	VALVE APPLICATIONS										
	Microdots	Dots	Jetting	Potting	Encapsulating	Lines/Stripes	Filling / Packaging	Microspray	Spray	Internal Spray	Internal Band
Optical Dyes / Lacquers	702M-SS	702M-SS	PICO Ppulse / XP	—	—	702M-SS	—	—	—	—	—
Primers	xQR41	—	PICO Ppulse / XP P-Jet	—	—	—	—	781Mini	—	782RA	—
Reagents	754V-SS ¹	754V-SS ¹	PICO Ppulse / XP P-Jet	—	—	754V-SS ¹	754V-SS ¹	781Mini	781S-SS	—	—
RTV/Sealants <i>low pressure</i>	xQR41	725DA-SS	P-Jet P-Dot	725DA-SS	725DA-SS	725DA-SS	725HF-SS	—	—	—	—
RTV/Sealants <i>medium / high pressure</i>	xQR41 ²	736HPA-NV	P-Jet P-Dot	736HPA-NV	736HPA-NV	736HPA-NV	736HPA-NV	—	—	—	—
Saline	—	754V-SS ¹	PICO Ppulse / XP P-Jet	—	—	754V-SS ¹	754V-SS ¹	—	—	—	—
Silicones	—	736HPA-NV	PICO Ppulse / XP P-Jet, P-Dot	736HPA-NV	736HPA-NV	736HPA-NV	—	781Mini	781S-SS	—	—
Silicone Oils	xQR41 741MD	xQR41V 741V-SS	PICO Ppulse / XP P-Jet, P-Dot	—	—	xQR41V 741V-SS	—	—	—	—	—
Solder Resists	—	725DA-SS	PICO Ppulse / XP P-Jet, P-Dot	—	—	725DA-SS	725HF-SS	—	—	—	—
Solvents	xQR41 741MD	xQR41V 741V-SS	PICO Ppulse / XP P-Jet	—	—	xQR41V 741V-SS	752V-UHSS	781Mini	781S-SS	782RA	7860C-RS
Solder Pastes	794	794	—	—	—	794	—	—	—	—	—
Thermal Interface Materials (TIM)	794-TC	794-TC	—	—	—	794-TC	—	—	—	—	—
UV-cure & Light-cure	xQR41 741MD	752V-SS	PICO Ppulse / XP P-Jet, P-Dot	752V-SS	752V-SS	xQR41V 752V-SS	725HF-A	—	—	—	—
UV-Cure with Anaerobics	xQR41 752V-SS	xQR41 752V-SS	PICO Ppulse / XP P-Jet	752V-SS	752V-SS	752V-SS	725HF-A	—	—	—	—
Water	xQR41	752V-UHSS	PICO Ppulse / XP P-Jet	—	—	xQR41V 741V-SS	752V-UHSS	781Mini	781S-SS	782RA	7860C-RS
White Glue	—	725DA-SS	P-Jet	—	—	725DA-SS	725HF-SS	—	—	—	7860C-RS

¹ Important Note: For dispensing applications of low- to medium-viscosity fluids where a 316L SS wetted fluid body with aseptic fluid flow path is preferred, choose the 754V-SS diaphragm valve.
² xQR41 for medium pressure only.

Maximum operating temperatures of EFD valves should not exceed 43° C (110° F) except for the 736HPA-NV, 741V, 781S, and 781Mini Series valves, which can operate up to 110° C (215° F).

VALVE FEATURES	VALVES															
																
	PICO Pulse / Pμlse XP	Liquidyn	702M-SS	725DA-SS	725HF-SS	725HF-A	736HPA-NV	xQR41 / V 741V / MD	752V-SS	752V-UHSS	754V-SS	781Mini 787MS-SS	781S-SS	782RA	7860C-RS	794 794-TC
Adjustable fluid flow	✓	P-Jet	✓	✓	–	–	–	✓	✓	✓	✓	✓	✓	✓	–	✓
Air cutoff	–	✓	–	–	–	–	–	–	–	–	–	✓	✓	✓	✓	–
Cycle rate ≥ 150Hz	1000Hz ¹	P-Jet P-Dot	–	–	–	–	–	–	–	–	–	–	–	–	–	–
Fail-safe normally closed	–	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	–	–
FDA-compliant wetted parts	–	–	✓	✓	✓	✓	–	✓	✓	✓	✓	✓	✓	–	✓	–
Fluid body	303 SS ⁶	303 SS ⁶	303 SS	303 SS	303 SS	Acetal	303 SS	303 SS ⁴	Acetal ⁷	UHMW ² / ⁷	316L	303 SS	303 SS	–	–	440C / Tungsten Carbide
Modular design	✓	✓	–	–	–	–	–	xQR41 / V	–	–	–	✓ ⁵	–	–	–	–
Quick Release maintenance	✓	–	–	–	–	–	–	xQR41 / V	–	–	–	✓ ⁵	–	–	–	✓
Small form factor	–	–	✓	–	–	–	–	xQR41 / V	–	–	–	✓ ⁵	–	–	–	–
Snuff-back cutoff	–	–	–	✓	✓	✓	✓	–	–	–	–	–	–	–	–	✓
Stroke control reference	–	–	✓	–	–	–	–	✓	✓	✓	✓	✓	✓	✓	–	–
Tamper-resistant stroke control	–	–	✓	–	–	–	–	○ ³	○	✓	✓	–	○	○	–	–
UHMW ² polymer diaphragm	–	–	✓	✓	✓	✓	–	–	✓	✓	PTFE	–	–	–	–	–
303 stainless steel air cylinder	–	–	✓	–	–	–	✓	xQR41 741V-SS	✓	✓	316L	✓	✓	–	–	–

¹ With approved conditional settings ² Ultra High Molecular Weight polyethylene ³ 741V-SS model only ⁴ Available with PEEK fluid body for xQR41 model only
⁵ 781Mini model only ⁶ Available with PEEK fluid body for PICO Pμlse, P-Dot, and P-Jet ⁷ Optional stainless steel fluid body

✓ Applicable | ○ Optional | – Not applicable

CONTROLLER FEATURES	VALVE CONTROLLERS							
	PICO Touch / XP	V200	8000	8040	7160RA	7194	7100	7140
	Jet Valve Control	Jet Valve Control	Multi Valve Control	Multi Spray Valve Control	Radial Spinner/ Spray Valve Control	Auger Valve Control	Dispense Valve Control	Spray Valve Control
Recommended valve(s)	PICO Pulse / XP	P-Jet, P-Dot	702, 725, 736, 741, 752, 754, xQR41 / V	781S, 781Mini, 787MS	782RA, 7860C-RS Spinner	794, 794-TC	702, 725, 736, 741, 752, 754, xQR41 / V	781S, 781Mini, 787MS
Air pressure display	Touchscreen	Digital	Analog	Analog	Digital	Digital	Digital	Analog
Auto sequence mode	—	—	—	—	—	—	—	—
Cycle rate	1000Hz ¹	280Hz / 150Hz	>600/minute	>400/minute	>400/minute	>400/minute	>600/minute	>400/minute
Digital time set and display	✓	✓	✓	✓	✓	✓	✓	✓
Dual 24W temperature control	—	—	—	—	—	—	—	—
5-micron filter/regulator	—	—	Included	Included	Included	Included	Included	Included
I/O communication-PLC	✓	✓	—	—	—	—	—	—
I/O interface circuitry	✓	✓	✓	✓	✓	✓	✓	✓
Independent multi-valve control	Single channel	Single channel	4-channel control	2-channel control	Single channel	Single channel	Single channel	Single channel
Low air pressure sensing	✓	—	< 4.1 bar (60 psi)	< 4.1 bar (60 psi)	< 4.1 bar (60 psi)	< 4.1 bar (60 psi)	< 4.1 bar (60 psi)	< 4.1 bar (60 psi)
Nozzle air shutoff delay	—	—	—	Adjustable 0 to 9.99 sec.	Adjustable 0 to 2.5 sec.	—	—	Adjustable 0 to 9.99 sec.
On the fly adjustability	✓	✓	✓	✓	✓	✓	✓	✓
Panel mount/panel cutout size	142 x 133 mm (5.6 x 5.25")	450 x 125 mm (18 x 5")	183.6 x 51.6 mm (7.23 x 2.03")	183.6 x 51.6 mm (7.23 x 2.03")	226.3 x 68.8 mm (8.91 x 2.71")	226.3 x 68.8 mm (8.91 x 2.71")	142.9 x 68.8 mm (5.62 x 2.71")	205.4 x 68.8 mm (8.08 x 2.71")
Pre-dispense time cycle delay	—	—	✓	—	—	—	—	—
Programmable	✓ ²	✓	✓	✓	✓	✓	✓	✓
Purge control	✓	✓	✓	✓	✓	✓	✓	✓
Spike & hold capability	—	—	—	—	—	—	—	—
Test cycle verification	✓	✓	✓	✓	✓	✓	✓	✓

¹ With approved conditional settings ² Programmable lockout

✓ Applicable | ○ Optional | — Not applicable

Useful Resources

Choosing and implementing the best possible fluid dispensing equipment starts with access to the best possible resources. Here are some to get you started:



Application Videos

Visit our Video Gallery to access 150+ application, how-to, and product videos.

See EFD dispensing solutions in action.

Watch Videos: www.nordsonefd.com/VideoGallery



What Our Customers Say

Find out how Nordson EFD helps manufacturers improve their fluid dispensing processes every day – see what our customers have to say.

Our Customers Know Best: www.nordsonefd.com/Testimonials



Expert Recommendations

Knowledgeable Nordson EFD fluid application specialists have, on average, more than 10 years of experience helping customers find the right dispensing solutions.

Request Expert Advice: www.nordsonefd.com/Advice

Request Lab Test: www.nordsonefd.com/ApplicationTest

Follow our Blog: www.nordsonefd.com/Blog



Easy Part Number Search

It's easy to search our digital catalog to find products by part number or keywords. Plus, get links to product specs, videos, and more. With our app, you can even access the catalog from your smartphone.

Find Part Numbers: www.nordsonefd.com/Digital-Catalog



Machine Builder Guide & CAD Models

When you partner with Nordson EFD, you benefit from a wide range of reliable, best-in-class precision fluid dispensing solutions.

Learn more: www.nordsonefd.com/MachineBuilderGuide

Download CAD models: www.nordsonefd.com/CAD



For Nordson EFD sales and service in over 40 countries, contact Nordson EFD or go to www.nordsonefd.com.

Global

800-556-3484; +1-401-431-7000
info@nordsonefd.com

Europe

00800 7001 7001
infoefd.europe@nordsonefd.com

Asia

China: +86 (21) 3866 9006; china@nordsonefd.com
India: +91 80 4021 3600; india@nordsonefd.com
Japan: +81 03 5762 2760; japan@nordsonefd.com
Korea: +82-31-736-8321; korea@nordsonefd.com
SEAsia: +65 6796 9522; sin-mal@nordsonefd.com

©2024 Nordson Corporation v011724